



TREMGLAZE® LEF FOAM

FEATURES AND BENEFITS

- Versatile and dependable
- One-component
- Perimeter sealing foam with low expansion
- Designed for window and door new construction, replacement, and retrofit installations
- Reduces air infiltration and prevents heat loss in a variety of applications
- Recommended application temperature is from 14 to 94 °F (-10 to 35 °C), which allows for application all year round

Tremco LEF Figures	
Weight of Can	680 g
Volume of Can	24 oz.
Yield in L	42 L
Expansion Rate	Rate of expansion allows for faster install and removes the possibility for joint disruption.

PU PRO APPLICATOR

- Part Number: 001798MG501
- Heavy-duty gun that provides durability and total control
- All-aluminum construction
- Lightweight and compact
- Corrosion and wear-resistant
- Ergonomically-designed for comfort during extended use
- Spring trigger for accurate flow control



PU CONTRACTOR APPLICATOR

- Part Number: 001701MG501
- Plastic and metal combination
- Lightweight and compact
- Economic choice
- Spring trigger for accurate flow control
- Standard screw thread design for bead size adjustment and flow control



PU STANDARD APPLICATOR

- Part Number: 001798PG501
- All-plastic design
- Highly cost-effective, "disposable" choice
- Standard screw thread design for bead size adjustment and flow control



PU FOAM CLEANER

- Part Number: 001922GC501
- Packaging: 12 per case
- Pre-pressurized in an aerosol spray can
- Dispenses in the upright or inverted position
- Evaporates quickly
- Can be fitted directly to a PU foam gun, or used as a handheld aerosol can



PU FOAM APPLICATOR TIPS

- Part Number: 001400 501
- Replacement tips for PU applicator guns
- Color: White
- Packaging: 50/box



3735 Green Road • Beachwood, OH 44122 • 800.321.7906 • 216.292.5000
 1451 Jacobson Avenue • Ashland, OH 44805 • 800.321.2050 • 419.289.2050
 220 Wicksteed Avenue • Toronto, ON M4H 1G7 • 800.363.3213 • 416.421.3300